



TR-01

型号: TR-01

转速: 16rpm

环境温度: 4~60°C

外形尺寸: 225x148x195mm

功率: 4W



TR-02U

型号: TR-02U

转速: 10~40rpm

环境温度: 4~60°C

外形尺寸: 260x148x195mm

功率: 10W

试管旋转混匀器附件



10ml/15ml试管板x2 (TRA01)

0.5ml/0.8ml试管板x2 (TRA04)

磁板附件x1 (TRA07)

5ml/7ml试管板x2 (TRA02)

50ml试管板x1 (TRA05)

磁板压条x4 (TRA08)

1.5ml/2ml试管板x2 (TRA03)

50ml试管组合件x1 (TRA30)

支架x1 (TRA31)

参数

产品型号	TR-01	TR-02U
产品名称	试管旋转混匀器	
主要区别特征	固定转速	速度显示, 转速可调
转速	16rpm	10~40rpm
容量	84 x0.5ml 试管, 60 x1.5ml / 2.0ml 试管, 28 x5ml / 7ml 试管, 24x10ml 试管, 6x50ml 试管	
标配	试管支架: 2xTRA01、2xTRA02、2xTRA03、2xTRA04、1xTRA05	
来电自动恢复功能	有	
环境温度	4°C~60°C	
外形尺寸 (WxDxH)	225x148x195mm	260x148x195mm
功率	4W	10W
电源	AC220±22V 50±1Hz	AC100~240V 50~60Hz
净重	0.8kg	1kg
认证	CE, RoHS, WEEE	CE, RoHS, WEEE, cCSAus

附件

名称	型号	个/包	图片
10ml/15ml试管夹具	TRA01(标配)	2	
5ml/7ml试管夹具	TRA02(标配)	2	
1.5ml/2ml试管夹具	TRA03(标配)	2	
0.5ml/0.8ml试管夹具	TRA04(标配)	2	
50ml I 试管夹具	TRA05(标配)	1	
磁板附件	TRA07(选配)	1	
磁板压条	TRA08 (选配)	4	
50ml试管组合件	TRA30 (标配)	1	
支架	TRA31 (标配)	1	